
(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau





PCT



(10) International Publication Number WO 2004/055884 A1

(51) International Patent Classification7: H01L 21/336, 29/78, 29/423

(21) International Application Number:

PCT/IB2003/006026

- (22) International Filing Date: 8 December 2003 (08.12.2003)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0229210.0 0324099.1

14 December 2002 (14.12.2002) GB

15 October 2003 (15.10.2003)


- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): IN 'T ZANDT,


Michael, A., A. [NL/NL]; c/o Philips Intellectual Property & Standards, Cross Oak Lane, Redhill, Surrey RH1 5HA (GB). HIJZEN, Erwin, A. [NL/BE]; c/o Philips Intellectual Property & Standards, Cross Oak Lane, Redhill, Surrey RH1 5HA (GB).

- (74) Agent: SHARROCK, Daniel, J.; Philips Intellectual Property & Standards, Cross Oak Lane, Redhill, Surrey RH1 5HA (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: MANUFACTURE OF TRENCH-GATE SEMICONDUCTOR DEVICES





WO 2004/055884 A1

(57) Abstract: A method of manufacturing a trench-gate semiconductor device (1), the method including forming trenches (20) in a semiconductor body (10) in an active transistor cell area of the device, the trenches (20) each having a trench bottom and trench sidewalls, and providing silicon oxide gate insulation (21) in the trenches such that the gate insulation (33) at the trench bottoms is thicker than the gate insulation (21) at the trench sidewalls in order to reduce the gate-drain capacitance of the device. The method includes, after forming the trenches (20), the steps of: (a) forming a silicon oxide layer (21) at the trench bottoms and trench sidewalls; (b) depositing a layer of doped polysilicon (31) adjacent the trench bottoms and trench side walls; (c) forming silicon nitride spacers (32) on the doped polysilicon (21) adjacent the trench sidewalls leaving the doped polysilicon exposed at the trench bottoms; (d) thermally oxidising the exposed doped polysilicon to grow said thicker gate insulation (33) at the trench bottoms; (e) removing the silicon nitride spacers (32); and (f) depositing gate conductive material (34) within the trenches to form a gate electrode for the device. The final thickness of the thicker gate insulation (33) at the trench bottoms is well controlled by the thickness of the layer of doped polysilicon (31) deposited in step (b). Also the doped (preferably greater than 5e19cm-3) polysilicon oxidises fast at low temperatures (preferably 700-800°C), reducing the risk of diffusing (e.g. p body) implantations present in the device at that stage.

D

Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD,

SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.